GLOBAL TIRES INTERNATIONAL

UNITED STATES: 621 NW 53rd Street, Suite 125 Boca Raton Florida 33487
Tel: +1 5616541071

Gtiresinternational.us



TRUCK&BUS TIRES

Aonaite

7.50R16LT





899 ASR13



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
899	14	122/118	L	6.00G	16.0	1500/1320	770	DRIVING
ASR13	16	125/121	L	6.00G	14.0	1650/1450	870	All POSITION

8.25R16LT





899



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
899	16	128/124	L	6.50H	16.0	1800/1600	770	DRIVING

9.00R20





896 897



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	16	144/142	K	7.00	15.5	2800/2650	900	All POSITION
897	16	144/142	K	7.00	15.5	2800/2650	900	All POSITION

9.5R17.5





ASR37 DM55



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	143/141	L	6.75	13.5	2725/2575	875	DRIVING
DM55	18	143/141	L	6.75	15.0	2725/2575	875	STEER&TRAILER

10.00R20





896 897



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	18	149/146	K	7.50	16.5	3250/3000	930	All POSITION
897	18	149/146	K	7.50	16.5	3250/3000	930	All POSITION



11.00R20





896 896+ 897 897+ 899 696



686 868 807 809 YL919



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	18	152/149	K	8.00	17.0	3550/3250	930	All POSITION
896+	18	152/149	K	8.00	17.0	3550/3250	930	All POSITION
897	18	152/149	K	8.00	17.0	3550/3250	930	All POSITION
897+	18	152/149	K	8.00	17.0	3550/3250	930	All POSITION
899	18	152/149	K	8.00	19.0	3550/3250	930	All POSITION
696	18	152/149	K	8.00	15.0	3550/3250	930	STEER&TRAILER
686	18	152/149	K	8.00	16.0	3550/3250	930	DRIVING
868	18	152/149	K	8.00	19.0	3550/3250	930	DRIVING
807	18	152/149	K	8.00	23.0	3550/3250	930	DRIVING
809	18	152/149	E	8.00	23.0	3550/3250	930	DRIVING
YL919	18	152/149	E	8.00	21.5	3550/3250	930	DRIVING

12.00R20





896 896+ 897 899 ZY81



868 807 YL919 TK132



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	20	156/153	K	8.50	17.5	4000/3650	900	All POSITION
896+	20	156/153	K	8.50	17.5	4000/3650	900	All POSITION
897	20	156/153	K	8.50	17.5	4000/3650	900	All POSITION
899	20	156/153	K	8.50	19.0	4000/3650	900	All POSITION
ZY81	20	156/153	J	8.50	17.0	4000/3650	900	All POSITION
868	20	156/153	K	8.50	19.0	4000/3650	900	DRIVING
807	20	156/153	K	8.50	23.0	4000/3650	900	DRIVING
YL919	20	156/153	E	8.50	21.5	4000/3650	900	DRIVING
TK132	20	156/153	E	8.50	26.0	4000/3650	900	DRIVING

12.00R24





896 828 982



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	20	160/157	K	8.50	15.0	4500/4125	900	All POSITION
828	20	160/157	K	8.50	14.5	4500/4125	900	All POSITION
982	20	160/157	K	8.50	14.5	4500/4125	900	STEER&TRAILER

11R22.5





896 698 699 903 ASR37 ATR66



668 DM55 ADR535 SUPER DL23 SUPER DM7



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	18	148/145	M	8.25	15.0	3150/2900	850	All POSITION
698	18	148/145	M	8.25	15.0	3150/2900	850	STEER&TRAILER
699	16	146/143	M	8.25	16.0	3000/2725	830	STEER&TRAILER
903	18	148/145	M	8.25	18.0	3150/2900	850	STEER&TRAILER
ASR37	18	148/145	M	8.25	13.5	3150/2900	850	STEER&TRAILER
ATR66	18	148/145	M	8.25	14.5	3150/2900	850	STEER&TRAILER
668	16	146/143	L	8.25	20.0	3000/2725	830	DRIVING
DM55	18	148/145	M	8.25	21.5	3150/2900	850	DRIVING
ADR535	18	148/145	M	8.25	19.5	3150/2900	850	DRIVING
SUPER LD23	18	148/145	L	8.25	23.0	3150/2900	850	DRIVING
SUPER DM7	18	148/145	L	8.25	23.0	3150/2900	850	DRIVING

12R22.5





668 886 DM55 ADR527 669



896 TM161 699 YL662



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
668	18	152/149	L	9.00	20.0	3550/3250	930	DRIVING
886	18	152/149	L	9.00	18.0	3550/3250	930	DRIVING
DM55	18	152/149	L	9.00	22.5	3550/3250	930	DRIVING
ADR527	18	152/149	J	9.00	22.5	3550/3250	930	DRIVING
669	18	152/149	L	9.00	19.0	3550/3250	930	All POSITION
896	18	152/149	M	9.00	17.0	3550/3250	930	All POSITION
TM161	18	152/149	L	9.00	17.0	3550/3250	930	All POSITION
699	18	152/149	M	9.00	16.5	3550/3250	930	STEER&TRAILER
YL662	18	152/149	M	9.00	15.0	3550/3250	930	STEER&TRAILER

11R24.5





ASR37 ADR535



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	149/146	M	8.25	13.5	3250/3000	830	STEER&TRAILER
ADR535	18	149/146	M	8.25	19.5	3250/3000	830	DRIVING

13R22.5





896



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
896	18	154/151	L	9.75	17.5	3750/3450	830	All POSITION

215/75R17.5





ASR37 ADR553 ECOSMART78



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	135/133	L	6.00	12.0	2180/2060	860	STEER&TRAILER
ADR553	18	135/133	L	6.00	15.5	2180/2060	860	DRIVING
ECOSMART78	18	135/133	L	6.00	15.5	2180/2060	860	DRIVING

235/75R17.5





ASR37 ADR553 ECOSMART78



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	143/141	L	6.75	13.0	2725/2575	900	STEER&TRAILER
ADR553	18	143/141	L	6.75	16.0	2725/2575	900	DRIVING
ECOSMART78	18	143/141	L	6.75	16.0	2725/2575	900	DRIVING

275/70R22.5





ASR37



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	146/143	L	8.25	14.0	3000/2725	900	STEER&TRAILER

275/80R22.5





ASR37



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ASR37	18	149/146	L	8.25	14.0	3250/3000	900	STEER&TRAILER

295/80R22.5





668 **ADR523** **698** **ASR37**



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
668	18	152/149	L	9.00	20.0	3550/3250	900	DRIVING
ADR523	18	152/149	L	9.00	20.0	3550/3250	900	DRIVING
698	18	152/149	M	9.00	15.0	3550/3250	900	STEER&TRAILER
ASR37	18	152/149	M	9.00	16.0	3550/3250	900	STEER&TRAILER

315/70R22.5





ECOSMART62 ECOSMART78 ADR569



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
ECOSMART62	18	152/148	M	9.00	15.0	3550/3150	830	STEER&TRAILER
ECOSMART78	18	152/148	M	9.00	20.0	3550/3150	830	DRIVING
ADR569	18	152/148	M	9.00	20.0	3550/3150	830	DRIVING

385/65R22.5





688 AAR707 AH398



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
688	24	164	K	11.75	14.5	5000	900	TRAILER
AAR707	24	164	K	11.75	15.0	5000	900	TRAILER
AH398	24	164	K	11.75	14.5	5000	900	STEER&TRAILER

315/80R22.5





668 886 ADR569 SUPER DM7 ADR778



698 ASR567 ASR32 828 896



TECHNICAL DATA								
PATTERN	PR	LOAD INDEX S | D	SPEED RATING	RIM	TREAD DEPTH (mm)	MAX.LOAD (Kg) S | D	PRESSURE (kPa)	RECOMMEND POSITION
668	20	156/150	L	9.00	20.0	4000/3350	850	DRIVING
886	20	156/150	L	9.00	20.0	4000/3350	850	DRIVING
ADR569	20	156/150	L	9.00	24.5	4000/3350	850	DRIVING
SUPER DM7	22	158/156	K	9.00	22.0	4250/4000	900	DRIVING
ADR778	22	158/156	J	9.00	22.0	4250/4000	900	DRIVING
698	20	156/150	M	9.00	15.0	4000/3350	850	STEER&TRAILER
ASR567	20	156/150	L	9.00	16.5	4000/3350	850	STEER&TRAILER
ASR32	20	156/150	M	9.00	15.0	4000/3350	850	STEER&TRAILER
828	20	156/150	M	9.00	15.0	4000/3350	850	All POSITION
896	20	156/150	M	9.00	16.0	4000/3350	850	All POSITION