SONIX



PRODUCT MANUAL

TRUCK BUS TIRES

HIGHWAY

CARGO RADIAL TRUCK TIRE

HIGHWAY





SX200



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
295/60R22.5	18	9.00	3550	3075	150/147	K	900	130	15	-



SX-X4




* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-



SX-W02



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	16	-



SX-W06



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	16	-



SX696



* Suitable for trucks Steer & Trailer Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	L	930	135	15	-



SX712



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	18	8.25	3150	2900	148/145	M	850	125	14	276
11R24.5	16	8.25	3250	3000	149/146	M	830	120	14	254
215/75R17.5	18	6.00	1700	1600	135/133	J	860	125	13	600
225/70R19.5	14	6.75	1800	1700	128/126	M	760	110	13	522
235/75R17.5	18	6.75	2725	2575	143/141	J	900	130	12.5	505
245/70R19.5	16	7.50	2240	2120	136/134	M	825	120	13	-
255/70R22.5	16	7.50	2500	2300	140/137	M	800	116	14	-
265/70R19.5	18	7.50	2725	2575	143/141	J	850	124	13	430
275/70R22.5	18	8.25	3150	2900	148/145	M	900	130	14	316
285/75R24.5	16	8.25	3000	2725	146/143	M	830	120	14	260
295/75R22.5	16	9.00	3000	2725	146/143	M	830	120	14	290



SX-X6



* Suitable for trucks Steer & Trailer Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-

HIGHWAY





SX-Y17



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	12	9.00	2725	2575	143/141	K	620	90	17	-
12R22.5	18	9.00	2725	2575	152/149	K	620	90	17	-
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-



SX998



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
315/80R22.5	20	9.00	4000	3350	156/150	L	850	125	16	218



SX-DH21



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
275/70R22.5	18	8.25	3150	2900	148/145	K	900	130	22	-



SX808



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	21	276
11R24.5	16	8.25	3250	3000	149/146	M	830	120	21	254
285/75R24.5	16	8.25	3000	2725	146/143	M	830	120	21	260
295/75R22.5	16	9.00	3000	2725	146/143	M	830	120	21	290



SX668



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	15	-
11R22.5	18	8.25	3150	2900	148/145	M	850	125	15	-
12R22.5	18	9.00	3550	3250	152/149	M	930	135	15	-
13R22.5	20	9.75	4000	3650	156/150	L	930	135	15	-
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	15	-



SX966



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	18	8.25	3150	2900	148/145	M	850	125	15	-
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	15	-
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	15	-
385/55R22.5	20	12.25	4500	-	160/158	L	900	130	15	-
385/65R22.5	20	11.75	4500	-	160/---	L	900	130	15	-



SX-Y27



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-

HIGHWAY





SX-K718



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-



SX-KY002



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-



SX-KY006



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	18	-



SX-KY008



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	20	-



SX202



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
295/60R22.5	18	9.00	3350	3075	150/147	K	900	130	15	-



SX-A33



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	17	-
295/80R22.5	18	9.00	3550	3250	152/149	L	900	130	17	-



SX736



* Suitable for trucks Trailer Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R24.5	16	8.25	3250	3000	149/146	M	830	120	11	-
285/75R24.5	16	8.25	3000	2725	146/143	M	830	120	11	-
295/75R22.5	16	9.00	3000	2725	146/143	M	830	120	11	-



SX977



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
385/65R22.5	20	11.75	4500	-	160/---	L	900	130	15	-
385/55R22.5	20	12.25	4500	-	160/158	L	900	130	15	-

HIGHWAY





SX-H51



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
245/70R19.5	18	7.50	2800	2650	144/142	J	900	130	15	-



SX-X2

* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	15	-



SX-RD02



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
245/70R19.5	18	7.50	2800	2650	144/142	J	900	130	16	-



SX661



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	16	-
12R22.5	18	9.00	3550	3250	152/149	M	930	135	18	240
13R22.5	18	9.75	3750	3450	154/151	M	830	120	20	226
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	18	260



SX762



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	15	276
12R22.5	18	9.00	3550	3250	152/149	M	930	135	17	240
275/80R22.5	16	8.25	3250	3000	149/146	M	850	125	14	290
295/60R22.5	18	9.00	3350	3075	150/147	M	900	130	15	-
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	15	254
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	16	240



SX762+



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	M	930	135	16	-





SX766



* Suitable for trucks Trailer Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
385/65R22.5	20	11.75	4500	-	160/---	K	900	130	15	198
425/65R22.5	20	12.25	5150	-	165/---	K	825	120	15	-
445/65R22.5	20	13.00	5800	-	169/---	K	900	130	15	-



SX706



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	15	-
11R22.5	18	8.25	3150	2900	148/145	M	850	125	15	-
12R22.5	18	9.00	3550	3250	152/149	M	930	135	15	-
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	15	-
315/70R22.5	20	9.00	3750	3350	154/150	L	900	131	15	-
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	15	-



SX-K768



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	17	-



SX989



* Suitable for trucks All Position(Mainly on Trailer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
385/55R22.5	20	12.25	4500	-	160/158	L	900	130	15	-
385/65R22.5	20	11.75	4500	-	160/---	L	900	130	15	-



SX773



* Suitable for trucks Steer & Trailer Position(Mainly on Steer)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	15	240



SX999



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
425/65R22.5	20	12.25	5150	-	165/---	J	825	120	18	-
445/65R22.5	20	13.00	5800	-	169/--	K	900	130	18	-





SX668 (SX668+)



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
10.00R20	18	7.50	3250	3000	149/146	L	930	135	17	280
11.00R20	18	8.0	3550	3250	152/149	L	930	135	17	260
11R22.5	18	8.25	3150	2900	148/145	M	850	125	15	276
11R24.5	16	8.25	3250	3000	149/146	M	830	120	15	250
12.00R20	20	8.50	4000	3650	156/153	L	900	130	17	228
12.00R24	20	8.50	4500	4125	160/157	K	900	130	18	196
12R22.5	18	9.00	3550	3250	152/149	M	930	135	16	-
12R24.5	18	9.00	3750	3450	154/151	K	930	135	16	220
13R22.5	20	9.75	4000	3650	156/153	L	930	135	17	226
265/70R19.5	18	7.50	2725	2575	143/141	M	850	124	15	430
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	15	240
325/95R24	22	9.0	4750	4500	162/160	K	930	135	18	196
6.50R16LT	12	5.50F	1060	925	110/105	M	670	100	10	810
7.00R16LT	14	5.50F	1320	1180	118/114	M	770	110	11	640
7.50R16LT	14	6.00G	1500	1320	122/118	L	770	110	13	600
8.25R16LT	16	6.50H	1800	1600	128/124	L	770	110	13	530
9.00R20	16	7.0	2800	2650	144/142	L	900	130	16	300



SX982



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R24	20	8.50	4500	4125	160/157	K	900	130	15	196



SX883



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.00	3550	3250	152/149	L	930	135	17	-
12.00R20	20	8.50	4000	3650	156/153	L	900	130	18	-



SX-S01



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	148/145	J	830	120	21	-



SX897



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R24	20	8.50	4500	4125	160/157	K	900	130	15	196



SX898



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R24	20	8.50	4500	4125	160/157	K	900	130	16	196
325/95R24	22	9.0	4750	4500	162/160	K	930	135	16	-

ON & OFF ROAD

CARGO RADIAL TRUCK TIRE





SX-M3



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	K	930	135	16	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	16	-
325/95R24	22	9.00	4750	4500	162/160	K	850	125	16	-



SX-M5 (SX-W5)



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	K	930	135	19	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	18	-



SX-007



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	19	-



SX-X8



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	20	-



SX703



* Suitable for trucks All Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	L	930	135	17	-
12.00R20	20	8.50	4000	3650	156/153	L	900	130	17	-



SX610



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	L	900	130	17	-



SX-X5



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	K	930	135	20	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	20	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	16	-

ON & OFF ROAD





SX-Y77



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	20	-



SX075



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	J	930	135	19	-



SX076



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	J	930	135	22	-



SX807



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	L	930	135	19	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	18	-
13R22.5	20	9.75	4000	3650	156/153	F	930	135	21	-



SX-D33



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
295/80R22.5	18	9.00	3550	3250	152/149	L	900	130	22	-



SX635




* Suitable for trucks Drive Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	L	900	130	18	-



SX-L88 (SX-L88+)



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
10.00R20	18	7.50	3250	3000	149/146	L	930	135	17	-
11.00R20	18	8.0	3550	3250	152/149	L	930	135	17	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	16	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	15	-
12.00R20	20	8.50	4000	3650	156/153	L	900	130	16	-
13R22.5	18	9.75	3750	3450	154/151	L	830	120	17	-
13R22.5	18	9.75	3750	3450	154/151	K	830	120	17	-

ON & OFF ROAD





SX-D856



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
315/70R22.5	20	9.00	3750	3350	154/150	L	900	131	20	-



SX665



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	M	930	135	22	240



SX657



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	F	930	135	21	-
12.00R20	20	8.50	4000	3650	156/153	F	900	130	21	-



SX667



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	F	900	130	21	-



SX-K688



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	K	930	135	19	260
12.00R20	20	8.50	4000	3650	156/153	K	900	130	19	220



SX663



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	M	930	135	19	240



SX-K668



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	K	930	135	19	-
11.00R20	18	8.0	3550	3250	152/149	K	930	135	18	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	19	-
12.00R20	20	8.50	4000	3650	156/153	K	900	130	18	-
12R22.5	18	9.00	3550	3250	152/149	K	930	135	18	-
13R22.5	18	9.75	3750	3450	154/151	K	830	120	18	-
13R22.5	18	9.75	3750	3450	154/151	L	830	120	18	220





SX869



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	K	900	130	19	208
13R22.5	20	9.75	4000	3650	156/153	F	930	135	21	-



SX577

* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
235/75R17.5	18	6.75	2725	2575	143/141	J	900	130	16.5	-
315/80R22.5	22	9.00	6000	5450	158/156	J	970	140	22	-
325/95R24	22	9.00	4750	4500	162/160	K	850	125	24	-



SX875



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	K	830	120	19	-
12R22.5	18	9.00	3550	3250	152/149	J	930	135	22	-



SX776



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	18	8.25	3150	2900	148/145	J	850	125	25	-
295/80R22.5	18	9.00	3550	3250	152/149	J	900	130	23	-



SX-K777



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12R22.5	18	9.00	3550	3250	152/149	K	930	135	22	-



SX888



* Suitable for trucks Drive Position

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	L	930	135	18	-
11R22.5	18	8.25	3150	2900	148/145	M	850	125	20	276
12.00R20	20	8.50	4000	3650	156/153	K	900	130	18	-
12R22.5	18	9.00	3550	3250	152/149	M	930	135	20	-
215/75R17.5	18	6.00	1700	1600	135/133	J	860	125	15	600
225/70R19.5	14	6.75	1800	1700	128/126	M	760	110	15	522
235/75R17.5	18	6.75	2725	2575	143/141	J	900	130	14.5	505
245/70R19.5	16	7.50	2240	2120	136/134	M	825	120	15	-
265/70R19.5	18	7.50	2725	2575	143/141	J	850	124	15	430
275/80R22.5	16	8.25	3250	3000	149/146	M	850	125	19	290
285/70R19.5	18	8.25	3350	3150	150/148	J	900	130	16	380
295/80R22.5	18	9.00	3550	3250	152/149	M	900	130	20	254
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	20	240





SX818



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
7.50R16LT	14	6.00G	1500	1320	122/118	L	770	110	16	600
8.25R16LT	16	6.50H	1800	1600	128/124	L	770	110	16	530
10.00R20	18	7.50	3250	3000	149/146	L	930	135	18	280
11.00R20	18	8.0	3550	3250	152/149	L	930	135	18	260
12.00R20	20	8.50	4000	3650	156/153	L	900	130	19	228



SX808



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	16	8.25	3000	2725	146/143	M	830	120	20	-
11R22.5	18	8.25	3150	2900	148/145	M	850	125	20	-



SX806



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11R22.5	18	8.25	3150	2900	148/145	M	850	125	20	-
12R22.5	18	9.00	3550	3250	152/149	M	930	135	20	-
295/80R22.5	18	9.00	3550	3250	152/149	L	900	130	20	-
315/80R22.5	20	9.00	4000	3350	156/150	L	850	125	20	-



SX803



* Suitable for trucks All Position(Main In Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
13R22.5	20	9.75	4000	3650	156/150	K	930	135	20	-
295/80R22.5	18	9.00	3550	3250	152/149	K	900	130	20	-
315/80R22.5	20	9.00	4000	3350	156/150	K	850	125	20	-
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	20	-



SX868



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
315/80R22.5	20	9.00	4000	3350	156/150	M	850	125	21	218



SX03



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
13R22.5	20	9.75	4000	3650	156/153	L	930	135	18	-



SX895



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
325/95R24	22	9.00	4750	4500	162/160	K	850	125	20	-



SX899



* Suitable for trucks Drive & Trailer Position (Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
315/80R22.5	20	9.00	4000	3350	156/150	L	850	125	22	218

MINING

CARGO RADIAL TRUCK TIRE

MINING





SX-X9



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	F	930	135	23	-
12.00R20	20	8.50	4000	3650	156/153	F	900	130	24	-



SX-K85



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	F	930	135	23	-
12.00R20	20	8.50	4000	3650	156/153	F	900	130	24	-



SX-G66



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	F	900	130	26	-



SX885



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	E	930	135	23	238



SX886



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	E	930	135	25	238
12R22.5	18	9.0	3550	3250	152/149	E	930	135	25	208



SX988



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	E	900	130	26	-



SX93



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
11.00R20	18	8.0	3550	3250	152/149	E	930	135	25	-
11.00R20	18	8.0	3550	3250	152/149	F	930	135	25	-
12.00R20	20	8.50	4000	3650	156/153	F	900	130	26	-



SX-G99



* Suitable for trucks All Position(Mainly on Drive)

Size	Ply Rating	Rim	Max load (kg)		Load Index	Speed Rating	A.P.		Tread Depth (mm)	QTY
			Single	Dual			kPa	psi		PCS/40HQ
12.00R20	20	8.50	4000	3650	156/153	F	900	130	26	-

Comparison Table Of Speed Symbols And Maximum Driving Speed

Speed Symbol	Max. Speed (km/h)
A8	40
B	50
C	60
D	65
E	70
F	80
G	90
J	100
K	110
L	120
M	130

Correspondence Table Of Load Index And Tire Load Capacity

Load Index	Load Capacitty (kg)	Load Index	Load Capacitty (kg)	Load Index	Load Capacitty (kg)
100	800	124	1600	148	3150
101	825	125	1650	149	3250
102	850	126	1700	150	3350
103	875	127	1750	151	3450
104	900	128	1800	152	3550
105	925	129	1850	153	3650
106	950	130	1900	154	3750
107	975	131	1950	155	3875
108	1000	132	2000	156	4000
109	1030	133	2060	157	4125
110	1060	134	2120	158	4250
111	1090	135	2180	159	4375
112	1120	136	2240	160	4500
113	1250	137	2300	161	4625
114	1180	138	2360	162	4750
115	1215	139	2430	163	4875
116	1250	140	2500	164	5000
117	1285	141	2575	165	5150
118	1320	142	2650	166	5300
119	1360	143	2725	167	5450
120	1400	144	2800	168	5600
121	1450	145	2900	169	5800
122	1500	146	3000	170	6000
123	1550	147	3075	--	--

Use And Maintenance Of Tires

01 Keep The Air Pressure Normal

Tire inflation pressure is the main factor that determines the service life and working quality of the tire. When in use, it should be inflated according to the tire pressure standard, otherwise it will cause early wear and damage to the tire.

02 Tire Overload Is Strictly Prohibited

When the tire is overloaded, it will have a greater impact on the tire damage. When the tire is overloaded, the tire deformation will increase, and the stress of the cord will increase, which will easily cause the cord to break, loosen, and delaminate.

03 Master Vehicle Speed And Control Tire Temperature

You must insist on driving at medium speed. In summer, you should increase the number of stops. For example, if the tire heats or the internal pressure increases, you should stop to rest and cool down. It is strictly prohibited to deflate to reduce the tire pressure.

04 Reasonable Match Tires

According to the driving road conditions, the appropriate tread pattern is selected, and it is required to install the tires of the same brand, the same specification and the same level on the same axis.

05 Perform Daily Maintenance

Keep the car in good condition, and check it before leaving the car. Check whether the tire pressure is in compliance Check the rim nut for looseness? Clean up the tire stones and observe whether there is abnormal wear and damage? Transpose in time.